

ExxonMobil Escorene™ UL 02133EN2 Ethylene Vinyl Acetate Copolymer (European Grade)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Product Description: UL 02133EN12 is a copolymer of ethylene and vinyl acetate Availability: Africa & Middle East and Europe Additive: Antiblock: NoSlip: No Thermal Stabilizer: NoFree Flowing Agent: Yes Applications: Hot Melt Adhesives Wire and Cable Compounds Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-UL-02133EN2-Ethylene-Vinyl-Acetate-Copolymer-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.957 g/cc	0.0346 lb/in ³	ExxonMobil method
Vinyl Acetate Content	33 %	33 %	ExxonMobil method
Melt Flow	21 g/10 min	21 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65	65	Molded Properties; ASTM D2240
Tensile Strength at Break	>= 5.03 MPa	>= 730 psi	(20 in/min), Molded Properties; ASTM D638
Elongation at Break	>= 750 %	>= 750 %	(20 in/min), Molded Properties; ASTM D638
Tensile Modulus	0.00827 GPa	1.20 ksi	(0.2 in/min), Molded Properties; ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	<= 142 °C	<= 288 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China