

## ExxonMobil Exxsol™ D130 Dearomatized Fluid

Category : Fluid

**Material Notes:**

Availability: Asia Pacific, Central America, North America and South America  
Appearance: Clear/Transparent Liquid  
Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Exxsol-D130-Deaeromatized-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-D130-Deaeromatized-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.827 g/cc @Temperature 15.6 °C	0.0299 lb/in <sup>3</sup> @Temperature 60.0 °F	ASTM D4052
Vapor Pressure	<= 0.000133 bar @Temperature 20.0 °C	<= 0.100 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	279 °C	534 °F	Initial; ASTM D86
Flash Point	140 °C	284 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	190 °F	Method E, ASTM D611
Aromatic Content	0.01	ExxonMobil Method
Dry Point	595 °F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China