

## ExxonMobil Exxsol™ D60 Dearomatized Fluid

Category : Fluid

**Material Notes:**

Availability: Africa &amp; Middle East, Asia Pacific, Europe, Central America, North America and South America Appearance: Clear/Transparent

Liquid Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Exxsol-D60-Deaomatized-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-D60-Deaomatized-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.793 g/cc @Temperature 15.0 °C	0.0287 lb/in <sup>3</sup> @Temperature 59.0 °F	ASTM D4052
Kinematic Viscosity	1.68 cSt	1.68 cSt	ASTM D445
Vapor Pressure	<= 0.000533 bar @Temperature 20.0 °C	<= 0.400 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	185 °C	365 °F	Initial; ASTM D86
Flash Point	63.9 °C	147 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	158°F	Method E, ASTM D611
Aromatic Content	0.0005	ExxonMobil Method
Dry Point	419°F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China