

ExxonMobil Exxsol™ DSP100/120 Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East and Europe Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-DSP100120-Deaomatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.736 g/cc @Temperature 15.0 °C	0.0266 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	0.72 cSt	0.72 cSt	ASTM D445
Vapor Pressure	0.0400 bar @Temperature 20.0 °C	30.0 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	104 °C	219 °F	Initial; ASTM D86
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	136°F	Method E, ASTM D611
Aromatic Content	20 wt ppm	ExxonMobil Method
Dry Point	246°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China