

ExxonMobil Exxsol™ Isohexane Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East, Asia Pacific and Europe Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-Isohexane-Deaeromatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.671 g/cc @Temperature 15.0 °C	0.0242 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	0.44 cSt	0.44 cSt	ASTM D445
Vapor Pressure	0.267 bar @Temperature 20.0 °C	200 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	57.8 °C	136 °F	Initial; ASTM 1078
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aromatic Content	<10 wt ppm	UV, ExxonMobil Method
Dry Point	144°F	ASTM 1078

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China