

ExxonMobil Exxsol™ Isopentane S Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East, Asia Pacific and Europe Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-Isopentane-S-Deaeromatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.624 g/cc @Temperature 15.0 °C	0.0226 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	0.36 cSt	0.36 cSt	ASTM D445
Vapor Pressure	0.800 bar @Temperature 20.0 °C	600 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	27.2 °C	81.0 °F	Initial; ASTM 1078
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aromatic Content	<10 wt ppm	UV, ExxonMobil Method
Dry Point	86°F	ASTM 1078

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China