

## ExxonMobil Exxsol™ Methylpentane Naphtha Dearomatized Fluid

Category : Fluid

**Material Notes:**

Availability: North America Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Exxsol-Methylpentane-Naphtha-Deaeromatized-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-Methylpentane-Naphtha-Deaeromatized-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.663 g/cc @Temperature 15.6 °C	0.0239 lb/in <sup>3</sup> @Temperature 60.0 °F	ASTM D4052
Kinematic Viscosity	0.49 cSt	0.49 cSt	ASTM D445
Vapor Pressure	0.267 bar @Temperature 20.0 °C	200 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	60.0 °C	140 °F	Initial; ASTM 1078
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	147°F	Method E, ASTM D611
Aromatic Content	0.002	ExxonMobil Method
Dry Point	145°F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China