

ExxonMobil Isopar™ G (EU) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. **Appearance:** Clear/Transparent Liquid
Availability: Africa & Middle East and Europe
Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-G-EU-Isoparaffin-Fluid.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------------------------------|---|-------------------|
| Density | 0.748 g/cc @Temperature 15.0 °C | 0.0270 lb/in ³ @Temperature 59.0 °F | ISO 12185 |
| Kinematic Viscosity | 1.14 cSt | 1.14 cSt | ASTM D445 |
| Vapor Pressure | 0.00267 bar @Temperature 20.0 °C | 2.00 torr @Temperature 68.0 °F | ExxonMobil Method |

| Thermal Properties | Metric | English | Comments |
|--------------------|---------|---------|--------------------|
| Boiling Point | 160 °C | 320 °F | Initial; ASTM D86 |
| Flash Point | 42.8 °C | 109 °F | Method A; ASTM D56 |

| Descriptive Properties | Value | Comments |
|------------------------|-----------|-----------------------|
| Aniline Point | 172°F | Method E, ASTM D611 |
| Aromatic Content | 20 wt ppm | UV, ExxonMobil Method |
| Dry Point | 343°F | ASTM D86 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China