

## ExxonMobil Isopar™ H (AM) Isoparaffin Fluid

Category : Fluid

**Material Notes:**

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Asia Pacific, Central America, North America and South America Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Isopar-H-AM-Isoparaffin-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-H-AM-Isoparaffin-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.759 g/cc @Temperature 15.6 °C	0.0274 lb/in <sup>3</sup> @Temperature 60.0 °F	ASTM D4052
Kinematic Viscosity	1.8 cSt	1.8 cSt	ASTM D445
Vapor Pressure	0.000667 bar @Temperature 20.0 °C	0.500 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	180 °C	356 °F	Initial; ASTM D86
Flash Point	53.9 °C	129 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	185°F	Method E, ASTM D611
Aromatic Content	10 wt ppm	ExxonMobil Method
Dry Point	370°F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China