

ExxonMobil Isopar™ L (EU) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Africa & Middle East and Europe Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-L-EU-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.764 g/cc @Temperature 15.0 °C	0.0276 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	1.64 cSt	1.64 cSt	ASTM D445
Vapor Pressure	0.000667 bar @Temperature 20.0 °C	0.500 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	186 °C	367 °F	Initial; ASTM D86
Flash Point	66.1 °C	151 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	178°F	Method E, ASTM D611
Aromatic Content	30 wt ppm	UV, ExxonMobil Method
Dry Point	406°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China