

ExxonMobil Isopar™ M (EU) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. **Appearance:** Clear/Transparent Liquid
Availability: Africa & Middle East and Europe
Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-M-EU-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.784 g/cc @Temperature 15.0 °C	0.0283 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	2.65 cSt	2.65 cSt	ASTM D445
Vapor Pressure	0.000107 bar @Temperature 20.0 °C	0.0800 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	206 °C	403 °F	Initial; ASTM D86
Flash Point	82.2 °C	180 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	187°F	Method E, ASTM D611
Aromatic Content	38 wt ppm	UV, ExxonMobil Method
Dry Point	491°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China