

## ExxonMobil Isopar™ N Isoparaffin Fluid

Category : Fluid

**Material Notes:**

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. Appearance:

Clear/Transparent Liquid Availability: Africa &amp; Middle East and Europe Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Isopar-N-Isoparaffin-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-N-Isoparaffin-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.788 g/cc @Temperature 15.0 °C	0.0285 lb/in <sup>3</sup> @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	3.02 cSt	3.02 cSt	ASTM D445
Vapor Pressure	<= 0.000133 bar @Temperature 20.0 °C	<= 0.100 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	218 °C	424 °F	Initial; ASTM D86
Flash Point	91.1 °C	196 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	189°F	Method E, ASTM D611
Aromatic Content	40 wt ppm	UV, ExxonMobil Method
Dry Point	496°F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China