

ExxonMobil LDPE LD 250 Low Density Polyethylene Resin (European Grade)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

Product Description: LD 250 is an LDPE extrusion coating grade, especially designed for low speed extrusion coating applications providing very low neck-in characteristics good heat sealing properties good organoleptic properties
Availability: Africa & Middle East and Europe
Additive: Antiblock: No Slip: No Thermal Stabilizer: No
Applications: Co-Extrusion Coating Demanding Heat Seals Extrusion Coating Extrusion Lamination Food packaging Low Neck In, Low Line Speed Coatings
 Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-LDPE-LD-250-Low-Density-Polyethylene-Resin-European-Grade.php

Physical Properties	Metric	English	Comments
Density	0.916 g/cc	0.0331 lb/in ³	ExxonMobil method
Melt Flow	5.0 g/10 min @Load 2.16 kg, Temperature 190 °C	5.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238
Neck In	3.05 cm @Temperature 315 °C	1.20 in @Temperature 599 °F	328 ft/min, Constant output at 35 rpm; ExxonMobil Method
	3.30 cm @Temperature 315 °C	1.30 in @Temperature 599 °F	82 ft/min, Constant output at 35 rpm; ExxonMobil Method
Drawdown	2.33 m/s @Temperature 315 °C	459 ft/min @Temperature 599 °F	Constant output at 35 rpm; ExxonMobil Method

Thermal Properties	Metric	English	Comments
Melting Point	<= 221 °C	<= 430 °F	Peak Melting Point; ExxonMobil method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China