

ExxonMobil MM Mobiltac Double Letter Series

Category: Fluid, Lubricant

Material Notes:

The Mobiltac Double Letter Series products are high performance, non-diluent type, heavy-bodied products intended for the lubrication of open gears over a wide range of environmental conditions and machine requirements. They incorporate extreme pressure additives for the protection of gear teeth and metal surfaces subject to extremely heavy loads. They form a cohesive and adhesive lubricating film that resists wear, water wash and excessive "throw off". They lubricate properly under boundary conditions. They resist peeling or flaking at subzero temperatures. Mobiltac Double Letter Series lubricants are recommended for all-purpose applications in open gears. The two lighter grades meet many builder requirements for heavily loaded splash-type enclosed gearing. Mobiltac Double Letter Series lubricants are recommended for all-purpose applications in open gears. The two lighter grades are used in heavily loaded splash-type enclosed gearing. Applications include: Machinery components as hoist gears, swing gears, large press gears; Equipment in forge shops, pit or strip mining; Large earthmoving equipment and cement kilns

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-MM-Mobiltac-Double-Letter-Series.php

| Physical Properties | Metric | English | Comments |
|-------------------------------------|----------|----------|-----------|
| Kinematic Viscosity at 40°C (104°F) | 3900 cSt | 3900 cSt | ASTM D445 |

| Thermal Properties | Metric | English | Comments |
|--------------------|--------|---------|----------|
| Flash Point | 182 °C | 360 °F | ASTM D92 |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China