

ExxonMobil Mobil 1 0W-30

Category : Fluid , Lubricant

Material Notes:

Mobil 1 W-30 is an advanced high performance synthetic engine oil designed to provide outstanding wear protection and enhanced fuel economy performance. Mobil 1 0W-30 exceeds the requirements of the latest industry standards required by newer modern gasoline and certain diesel powered automobile engines. Mobil 1 technology is race proven and is the choice of race car drivers around the world. Mobil 1 0W-30 is perfect for all types of driving anywhere in the world and has the performance to protect where conventional engine oils do not.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-1-0W-30.php

Physical Properties	Metric	English	Comments
Density	0.851 g/cc @Temperature 15.0 °C	0.0307 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Viscosity	2.99 cP @Temperature 150 °C	2.99 cP @Temperature 302 °F	High Temperature High Shear (HTHS); ASTM D4683
Viscosity Measurement	175	175	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	56 cSt	56 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	10.3 cSt	10.3 cSt	ASTM D445
Ash	1.2 %	1.2 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-54.0 °C	-65.2 °F	ASTM D97
Flash Point	234 °C	453 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China