

ExxonMobil Mobil 1 Synthetic ATF

Category : Fluid , Lubricant

Material Notes:

Mobil 1 Synthetic ATF is a multi-vehicle, fully synthetic fluid designed to meet the demanding requirements of modern passenger vehicles. Mobil 1 Synthetic ATF is a multi-vehicle formula recommended for use in modern high performance automobiles, SUVs, SUTs, vans and other light trucks requiring Dexron III , Ford Mercon and Mercon V performance levels; Also recommended by ExxonMobil for Chrysler automatic transmissions; Surpasses the off-highway power transmission requirements of Allison C-4; Suitable for Caterpillar TO-2 applications; Recommended for use in any power steering unit where a Dexron or Mercon fluid is recommended

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-1-Synthetic-ATF.php

Physical Properties	Metric	English	Comments
Brookfield Viscosity	5190 cP @Temperature -40.0 °C	5190 cP @Temperature -40.0 °F	ASTM D5293
Viscosity Measurement	199	199	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	34 cSt	34 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.6 cSt	7.6 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-54.0 °C	-65.2 °F	ASTM D97
Flash Point	236 °C	457 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	red	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China