

## ExxonMobil Mobil Clean 10W-40 5000

Category : Fluid , Lubricant

### Material Notes:

Mobil Clean 5000 is formulated from high quality base stocks combined with modern performance additives, including an advanced detergent system to provide excellent engine cleanliness at oil drain intervals up to 5,000 miles or 6 months, whichever comes first. These oils protect against sludge and engine rust and corrosion under severe and low-temperature operating conditions. Pour depressants and a viscosity index (VI) improver are included, where required, to provide the optimum viscosity and fluidity across a broad range of temperatures. Mobil Clean 5000 is available in four multi-viscosity grades: SAE 5W-20, 5W-30, 10W-30, and 10W-40. Mobil Clean 5000 5W-20 meets the latest requirements of Ford and Honda. It meets Ford Specification WSS-M2C930-A. Mobil Clean Oil 5W-20, 5W-30 and 10W-30 contain friction-reducing additives. The American Petroleum Institute (API) classifies these viscosity grades as "Energy Conserving" engine lubricants, and meet ILSAC GF-4. All four viscosity grades meet API SM and are backward compatible with earlier performance levels such as API SL,SH and SG. Mobil Clean 5000 5W-20 is recommended for vehicles which call for an API certified, 5W-20 viscosity grade engine oil such as 2001 and newer model year Ford automobiles, 1998 and newer model year Honda Accords, 1996 and newer Honda Civics and certain 2005 Chrysler vehicles. This unique viscosity grade should be used only in automobiles that require a 5W-20 lubricant and it is not recommended for use in other vehicles. This viscosity grade meets Ford WSS-M2C930A . Mobil Clean 5000 5W-30 and Mobil Clean 5000 10W-30 are recommended for gasoline fueled automobiles and light duty trucks requiring an API SM, SL or SJ product or API CF or CD. They meet ILSAC GF-4 (Starburst Certification Symbol). Mobil Clean 5000 10W-40 is recommended for gasoline fueled automobiles and light duty trucks where a higher viscosity oil is preferred or recommended and where an API SM, SL or SJ or API CF or CD product is required. Before using Mobil Clean 5000 performance motor oil, consult the owners manual of the vehicle for the manufacturers recommended viscosity grade and API Service Classification.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Mobil-Clean-10W-40-5000.php](http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Clean-10W-40-5000.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.876 g/cc	0.876 g/cc	
API Gravity	30 °	30 °	
Viscosity	6140 cP	6140 cP	CCS
	@Temperature -25.0 °C	@Temperature -13.0 °F	
Viscosity	20300 cP	20300 cP	MRV
	@Temperature -30.0 °C	@Temperature -22.0 °F	
Viscosity Measurement	147	147	Index
Kinematic Viscosity at 40°C (104°F)	102.1 cSt	102.1 cSt	
Kinematic Viscosity at 100°C (212°F)	14.55 cSt	14.55 cSt	

Thermal Properties	Metric	English	Comments
--------------------	--------	---------	----------

<small>Pour Point</small> Thermal Properties	<small>-36.0 °C</small> Metric	<small>-32.8 °F</small> English	Comments
Flash Point	200 °C	392 °F	

Descriptive Properties	Value	Comments
Energy Conserving	no	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China