

## ExxonMobil Mobil Clean 20W-50 Motor Oil

Category : Fluid , Lubricant

### Material Notes:

Mobil Clean Motor Oil is formulated from quality base stocks combined with the most modern performance additives, including an advanced detergent system to provide excellent engine cleanliness. These oils protect against sludge and engine rust and corrosion under low-temperature operating conditions. Pour depressants and a viscosity index (VI) improver are included, where required, to provide the desired viscosity-temperature and low-temperature fluidity characteristics. Mobil Clean Oil is available in five multi-viscosity grades: SAE 5W-20, 5W-30, 10W-30, 10W-40, and 20W-50 Mobil Clean Oil 5W-20 has been introduced to meet the latest requirements of Ford and Honda. It meets the latest Ford Specification WSS-M2C 930-A. Mobil Clean Oil 5W-20, 5W-30 and 10W-30 contain friction-reducing additives. These viscosity grades are classified by the American Petroleum Institute (API) as "Energy Conserving" engine lubricants, and meet ILSAC GF-4. Mobil Clean Oil 5W-20 is recommended for vehicles which call for an API certified, 5W-20 viscosity grade engine oil such as 2001 and newer model year Ford automobiles, 1998 and newer model year Honda Accords, and 1996 and newer Honda Civics. It is also recommended for 2005 Chrysler vehicles where a 5W-20 is recommended. This unique viscosity grade should be used only in automobiles that require a 5W-20 lubricant and it is not recommended for use in other vehicles. Mobil Clean Oil 5W-30 and Mobil Clean Oil 10W-30 are recommended for gasoline fueled automobiles and light duty trucks requiring an API SM, SL, SJ or SH product. They meet ILSAC GF-4 (Starburst Certification Symbol). Mobil Clean Oil 10W-40 is recommended for gasoline fueled automobiles and light duty trucks where a higher viscosity oil is preferred or recommended and where an API SM, SL, SJ or SH product is required. Mobil Clean Oil 20W-50 is recommended for high-performance engines found in race and rally driving. It has a higher viscosity reserve which provides engines with full protection under higher operating speeds, temperatures, and other adverse conditions. This product is also recommended for gasoline fueled automobiles and light trucks where a higher viscosity oil is preferred or recommended. Before using a Mobil Clean Oil, consult the owners manual of the vehicle for the manufacturers recommended viscosity grade and API Service Classification.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Mobil-Clean-20W-50-Motor-Oil.php](http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Clean-20W-50-Motor-Oil.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.890 g/cc	0.890 g/cc	
API Gravity	27.4 °	27.4 °	
Viscosity	8200 cP	8200 cP	CCS
	@Temperature -15.0 °C	@Temperature 5.00 °F	
	24000 cP	24000 cP	MRV
	@Temperature -20.0 °C	@Temperature -4.00 °F	
Viscosity Measurement	124	124	Index
Kinematic Viscosity at 40°C (104°F)	162 cSt	162 cSt	
Kinematic Viscosity at 100°C (212°F)	18.1 cSt	18.1 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-27.0 °C	-16.6 °F	
Flash Point	200 °C	392 °F	

Descriptive Properties	Value	Comments
Energy Conserving	no	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China