

ExxonMobil Mobil Delvac 50 1650

Category : Fluid , Lubricant

Material Notes:

Mobil Delvac 1630, 1640, and 1650 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac 1600 monogrades are used in a wide range of applications where a monograde lubricant is recommended. Naturally aspirated and turbo-charged diesel powered equipment; On-highway light and heavy-duty trucking; Off-highway industries including: construction, mining, quarrying, and agriculture

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Delvac-50-1650.php

Physical Properties	Metric	English	Comments
Density	0.896 g/cc @Temperature 15.0 °C	0.0324 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Viscosity Measurement	110	110	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	202 cSt	202 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	19.5 cSt	19.5 cSt	ASTM D445
Ash	1.4 %	1.4 %	Sulfated Ash, wt%; ASTM D874

Thermal Properties	Metric	English	Comments
Pour Point	-18.0 °C	-0.400 °F	ASTM D97
Flash Point	290 °C	554 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	12	12	mg KOH/g; ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China