

## ExxonMobil Mobil Delvac Synthetic ATF

Category : Fluid , Lubricant

**Material Notes:**

Mobil Delvac Synthetic ATF is a synthetic fluid designed that meets the demanding requirements of modern heavy duty automatic transmissions. The synthetic baseoil composition enables excellent performance even in the severest of operating conditions. It offers outstanding gear shifting and power transfer performance. Versus conventional ATF fluids, the inherently high viscosity index and stability of Mobil Delvac Synthetic ATF protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -54° C. Mobil Delvac Synthetic ATF is recommended for use in modern high performance trucks, buses, utility vehicles, haulers, vans and other equipment requiring Allison TES-295, Allison C-4 or Voith performance levels.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Mobil-Delvac-Synthetic-ATF.php](http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Delvac-Synthetic-ATF.php)

Physical Properties	Metric	English	Comments
Density	0.850 g/cc @Temperature 15.0 °C	0.0307 lb/in <sup>3</sup> @Temperature 59.0 °F	ASTM D4052
Brookfield Viscosity	8400 cP @Temperature -40.0 °C	8400 cP @Temperature -40.0 °F	ASTM D5293
Viscosity Measurement	168	168	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	39 cSt	39 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.3 cSt	7.3 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-54.0 °C	-65.2 °F	ASTM D97
Flash Point	236 °C	457 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	red	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China