

ExxonMobil Mobil Multi-Vehicle ATF

Category : Fluid , Lubricant

Material Notes:

Mobil Multi-Vehicle ATF is a premium synthetic blend lubricant formulated to provide excellent service in a wide variety of automotive automatic transmission applications. It is approved for use in vehicles that specify Ford MERCON®, MERCON® V, GM DEXRON® III (including the new GM DEXRON® III H specification), DEXRON® II E, or DEXRON® ATF. Mobil Multi-Vehicle ATF is recommended by ExxonMobil for Chrysler automatic transmissions. Mobil Multi-Vehicle ATF is recommended for Allison C-4 and Caterpillar TO-2 applications, as well as in any power steering unit that recommends a DEXRON® or MERCON® fluid. Mobil Multi-Vehicle ATF is a premium lubricant for car and truck automatic transmissions and other applications that require an automatic transmission fluid satisfying Ford MERCON®, MERCON® V, GM DEXRON® III, DEXRON® II E or DEXRON® ATF. Mobil Multi-Vehicle ATF is recommended by ExxonMobil for Chrysler automatic transmissions. It is generally recommended for automatic transmissions in General Motors and American Motors (now part of DaimlerChrysler Corporation) cars, vans, and light trucks and for imported cars such as Audi, Honda, Mazda, Nissan, Opel, Renault, Toyota and Volkswagen where a Dexron type fluid is recommended. Mobil Multi-Vehicle ATF is also recommended for automatic transmissions in all Ford Motor Company vehicles where MERCON ESP-M2C166H or ESP-M2C138CJ fluids are specified. For Ford automatic transmissions requiring M2C33-F (Type F) fluids, Mobil ATF Type F is recommended. Mobil Multi-Vehicle ATF meets the transmission fluid requirements for Allison automatic transmissions and other heavy-duty equipment that requires a Dexron-III fluid. It is approved against the Allison C-4 specification and therefore can be used in Allison Powershift transmissions or other torque converter systems that specify this type fluid. It is also recommended for Caterpillar TO-2 applications. Mobil Multi-Vehicle ATF is recommended for power steering units where the manufacturer recommends a DEXRON® or MERCON® fluid. Many car makers recommend against the use of automatic transmission fluids and, instead, require the use of their own power steering fluids to provide maximum hose life and to minimize pump squeal and wear. Mobil Multi-Vehicle ATF also can be used as the lubricating oil in several types of rotary air compressors under certain service conditions. Its low-temperature properties and resistance to oxidation are important factors in meeting the requirements of this service. Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Multi-Vehicle-ATF.php

Physical Properties	Metric	English	Comments
API Gravity	34.6 °	34.6 °	
Viscosity	12000 cP @Temperature -40.0 °C	12000 cP @Temperature -40.0 °F	
Viscosity Measurement	171	171	
Kinematic Viscosity at 40°C (104°F)	35 cSt	35 cSt	
Kinematic Viscosity at 100°C (212°F)	7.1 cSt	7.1 cSt	

Thermal Properties	Metric	English	Comments
Flash Point	180 °C	356 °F	

Descriptive Properties	Value	Comments
Color	red	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China