

ExxonMobil Mobil Velocite 8

Category: Fluid, Lubricant

Material Notes:

The Mobil Velocite Oil Numbered Series oils are premium performance products primarily designed for the lubrication of high-speed spindles in machine tools. They are also used in some critical hydraulic, circulation systems and air line oilers where the appropriate viscosity grade is selected. They are formulated from select high-quality, low viscosity base oils and additives that impart good resistance to oxidation and protection from rust and corrosion. They possess very good resistance to foaming and separate readily from water. High speed spindle bearings in machine tools and equipment where high speeds and fine clearances are involved; Precision grinders, lathes, jig borers and tracer mechanisms; Velocite Oil No 3 is recommended for "zero clearance" type spindle bearings which operate with extremely close clearances; For sleeve type spindle bearings having greater clearances, the choice of viscosity depends on the relation between clearance and spindle speed; Low pressure hydraulic systems where appropriate viscosity is selected; Air line oilers (Mobil Velocite Oil No. 10); For some sensitive instruments such as telescopes, laboratory equipment, etc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Velocite-8.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|----------------------|---------------------------|------------|
| Density | 0.854 g/cc | 0.0309 lb/in ³ | ASTM D4052 |
| | @Temperature 15.0 °C | @Temperature 59.0 °F | A31W104032 |
| Kinematic Viscosity at 40°C (104°F) | 15 cSt | 15 cSt | ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 3.28 cSt | 3.28 cSt | ASTM D445 |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|---------|----------|
| Pour Point | -9.00 °C | 15.8 °F | ASTM D97 |
| Flash Point | 194 °C | 381 °F | ASTM D92 |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|--------------------|
| Total Acid Number | 0.060 | 0.060 | mgKOH/g; ASTM D974 |

| Descriptive Properties | Value | Comments |
|----------------------------------|-------|---------------|
| Copper Strip Corrosion | 1A | 3 hrs @ 100°C |
| Rust Prevention, Distilled Water | pass | ASTM D665A |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China