

ExxonMobil Nappar™ 6 Naphthenic Fluid

Category : Fluid

Material Notes:

Appearance: Clear/Transparent Liquid Availability: Africa & Middle East and Europe Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Nappar-6-Naphthenic-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.759 g/cc @Temperature 15.0 °C	0.0274 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	0.86 cSt	0.86 cSt	ASTM D445
Vapor Pressure	0.107 bar @Temperature 20.0 °C	80.0 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	78.9 °C	174 °F	Initial; ASTM D1078
Flash Point	<= 0.000 °C	<= 32.0 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	99°F	Method E, ASTM D611
Aromatic Content	1 wt ppm	UV, ExxonMobil Method
Dry Point	181°F	ASTM D1078

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China