

ExxonMobil PP3155E3 Polypropylene Copolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

Product Description: A homopolymer resin designed for spunbond nonwovens. The resin is particularly suited for excellent spinning for uniform, high quality fabrics.
Availability: Asia Pacific **Features:** Good Processability **Uses:** Fibers Industrial Applications
Medical/Healthcare Applications Personal Care Spunbond Nonwovens **Processing Method:** Filament Extrusion and Spunbond Nonwovens
Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-PP3155E3-Polypropylene-Copolymer.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ExxonMobil Method
Melt Flow	36 g/10 min @Load 2.16 kg, Temperature 230 °C	36 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China