

## ExxonMobil PP3295G1 Polypropylene Homopolymer

Category : Polymer , Thermoplastic , Polypropylene (PP)

**Material Notes:**

**Product Description:** A free-flowing, ultrahigh melt flow rate homopolymer resin designed for meltblown nonwoven applications.  
**Availability:** North America **Features:** Good Processability **High Flow Uses:** Industrial Applications Nonwovens **Processing Method:** Fiber (Spinning) Extrusion  
Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-PP3295G1-Polypropylene-Homopolymer.php](http://www.lookpolymers.com/polymer_ExxonMobil-PP3295G1-Polypropylene-Homopolymer.php)

Physical Properties	Metric	English	Comments
Melt Flow	1000 - 1630 g/10 min @Load 2.16 kg, Temperature 230 °C	1000 - 1630 g/10 min @Load 4.76 lb, Temperature 446 °F	ExxonMobil Method

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China