

ExxonMobil Paxon™ EA55-003 Blow Molding Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Blow Molding Grade

Material Notes:

Product Description: EA55-003 is an unstabilized blow molding grade high density polyethylene copolymer. The base resin can be compounded to incorporate such things as stabilizers, fillers, and colorants before processing in order to meet the needs of the specific molding application.
Availability: Latin America, North America and South America
Additive: Thermal Stabilizer: Yes
Antistatic: No
Applications: Wood Plastic Containers
Information provided by ExxonMobil Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Paxon-EA55-003-Blow-Molding-Resin.php

Physical Properties	Metric	English	Comments
Density	0.954 g/cc	0.0345 lb/in ³	ASTM D4883
Melt Flow	0.43 g/10 min @Load 2.16 kg, Temperature 190 °C	0.43 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China