

ExxonMobil Solvesso™ 150 ND Aromatic Fluid

Category : Fluid

Material Notes:

Appearance: Clear/Transparent Liquid Availability: Africa & Middle East, Europe, Asia Pacific, Central America, North America and South America Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Solvesso-150-ND-Aromatic-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.886 g/cc @Temperature 15.0 °C	0.0320 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	1.17 cSt	1.17 cSt	ASTM D445
Vapor Pressure	0.000933 bar @Temperature 20.0 °C	0.700 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	179 °C	354 °F	Initial; ASTM D86
Flash Point	63.9 °C	147 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	61 °F	Mixed, Method E, ASTM D611
Aromatic Content	0.99	GC, ExxonMobil Method
Dry Point	381 °F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China