

ExxonMobil Solvesso™ 200 Aromatic Fluid

Category : Fluid

Material Notes:

Appearance: Transparent - Slight Yellow Liquid Availability: Africa & Middle East, Europe, Asia Pacific, Central America, North America and South America Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Solvesso-200-Aromatic-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.985 g/cc @Temperature 15.0 °C	0.0356 lb/in ³ @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	3.03 cSt	3.03 cSt	ASTM D445
Vapor Pressure	<= 0.000133 bar @Temperature 20.0 °C	<= 0.100 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	227 °C	441 °F	Initial; ASTM D86
	287 °C	549 °F	Final; ASTM D86
Flash Point	103 °C	217 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	59°F	Mixed, Method E, ASTM D611
Aromatic Content	0.99	GC, ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China