

ExxonMobil Vacmul O 3 D

Category: Fluid, Lubricant

Material Notes:

Vacmul O 3 D is a non-staining honing oil recommended for rough and finish honing of safety razor blades. It is suitable for light duty high speed applications and for use in large volume circulation systems where continuous filtration is employed.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Vacmul-O-3-D.php

| Physical Properties | Metric | English | Comments |
|-------------------------------------|------------|------------|------------|
| Specific Gravity | 0.847 g/cc | 0.847 g/cc | ASTM D1298 |
| Kinematic Viscosity at 40°C (104°F) | 6.0 cSt | 6.0 cSt | |
| ASTM Color | 8.0 | 8.0 | ASTM D1500 |

| Thermal Properties | Metric | English | Comments |
|--------------------|--------|---------|----------|
| Flash Point | 126 °C | 259 °F | ASTM D92 |

| Descriptive Properties | Value | Comments |
|------------------------|-------|---------------|
| Copper Strip Corrosion | 2A | 3 hrs @ 100°C |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China