

## ExxonMobil Varsol™ 40 Non-dearomatized Fluid

Category : Fluid

**Material Notes:**

Appearance: Clear/Transparent Liquid Availability: Africa &amp; Middle East and Europe Information provided by ExxonMobil

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ExxonMobil-Varsol-40-Non-dearomatized-Fluid.php](http://www.lookpolymers.com/polymer_ExxonMobil-Varsol-40-Non-dearomatized-Fluid.php)

Physical Properties	Metric	English	Comments
Density	0.786 g/cc @Temperature 15.0 °C	0.0284 lb/in <sup>3</sup> @Temperature 59.0 °F	ISO 12185
Kinematic Viscosity	1.16 cSt	1.16 cSt	ASTM D445
Vapor Pressure	0.00267 bar @Temperature 20.0 °C	2.00 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	158 °C	316 °F	Initial; ASTM D86
Flash Point	42.2 °C	108 °F	ASTM D56

Descriptive Properties	Value	Comments
Aniline Point	131 °F	Method E, ASTM D611
Aromatic Content	0.19	GC, ExxonMobil Method
Dry Point	378 °F	ASTM D86

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China