

Fainplast Compounds GA 63 Flexible PVC, Flame Retardant Sheathing

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

Material Notes:

Good flexibility

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-GA-63-Flexible-PVC-Flame-Retardant-Sheathing.php

Physical Properties	Metric	English	Comments
Density	1.38 - 1.42 g/cc	0.0499 - 0.0513 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	61 - 65	61 - 65	ISO R 868
Tensile Strength at Break	>= 10.0 MPa	>= 1450 psi	ISO R 527
Elongation at Break	>= 300 %	>= 300 %	ISO R 527

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-45.0 °C	-49.0 °F	Cold Flex; ISO 458/2

Descriptive Properties	Value	Comments
Thermal Stability (minutes)	65	CEI 20-34/3-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China