

Fainplast Compounds GA 89/3 Flexible PVC, Flame Retardant Sheathing

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

Material Notes:

Sheathing low emission acid fumes

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-GA-893-Flexible-PVC-Flame-Retardant-Sheathing.php

Physical Properties	Metric	English	Comments
Density	1.64 - 1.68 g/cc	0.0592 - 0.0607 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	87 - 91	87 - 91	ISO R 868
Tensile Strength at Break	>= 13.0 MPa	>= 1890 psi	ISO R 527
Elongation at Break	>= 200 %	>= 200 %	ISO R 527

Thermal Properties	Metric	English	Comments
Oxygen Index	28 %	28 %	ISO 4589

Descriptive Properties	Value	Comments
Thermal Stability (minutes)	150	CEI 20-34/3-2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China