

## Fainplast Compounds GS 650 Flexible PVC, Injection Molding for Footwear

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Molded

**Material Notes:**

Anti-slip soles

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Fainplast-Compounds-GS-650-Flexible-PVC-Injection-Molding-for-Footwear.php](http://www.lookpolymers.com/polymer_Fainplast-Compounds-GS-650-Flexible-PVC-Injection-Molding-for-Footwear.php)

Physical Properties	Metric	English	Comments
Density	1.17 - 1.21 g/cc	0.0423 - 0.0437 lb/in <sup>3</sup>	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	61 - 65	61 - 65	ISO R 868
Tensile Strength at Break	11.0 MPa	1600 psi	ISO R 527
Elongation at Break	410 %	410 %	ISO R 527
Abrasion	135	135	[mm <sup>3</sup> ]; DIN 53516

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-35.0 °C	-31.0 °F	Cold Flex; ISO 458/2

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China