

Fainplast Compounds PG 86/AF Flexible PVC, Extrusion Modified with Rubber

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

Material Notes:

Profiels UL 94 Classe V0

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-PG-86AF-Flexible-PVC-Extrusion-Modified-with-Rubber.php

Physical Properties	Metric	English	Comments
Density	1.28 - 1.32 g/cc	0.0462 - 0.0477 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	84 - 88	84 - 88	ISO R 868
Tensile Strength at Break	19.0 MPa	2760 psi	ISO R 527
Elongation at Break	240 %	240 %	ISO R 527

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-20.0 °C	-4.00 °F	Cold Flex; ISO 458/2
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China