

Fainplast Compounds PH 68/A Flexible PVC, Transparent Extrusion

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Transparent

Material Notes:

Profiles, UL Class V1

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-PH-68A-Flexible-PVC-Transparent-Extrusion.php

Physical Properties	Metric	English	Comments
Density	1.19 - 1.23 g/cc	0.0430 - 0.0444 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	66 - 70	66 - 70	ISO R 868
Tensile Strength at Break	16.0 MPa	2320 psi	ISO R 527
Elongation at Break	370 %	370 %	ISO R 527

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-32.0 °C	-25.6 °F	Cold Flex; ISO 458/2
Flammability, UL94	V-1	V-1	

Optical Properties	Metric	English	Comments
Transmission, Visible	90 %	90 %	transparent; thickness not quantified

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China