

Fainplast Compounds PM 6510/K Flexible PVC, Lead Free

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

Material Notes:

Pipes, UL 94 Class V1

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-PM-6510K-Flexible-PVC-Lead-Free.php

Physical Properties	Metric	English	Comments
Density	1.22 - 1.26 g/cc	0.0441 - 0.0455 lb/in ³	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	63 - 67	63 - 67	ISO R 868
Tensile Strength at Break	20.0 MPa	2900 psi	ISO R 527
Elongation at Break	360 %	360 %	ISO R 527

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-29.0 °C	-20.2 °F	Cold Flex; ISO 458/2
Flammability, UL94	V-1	V-1	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China