

Fainplast Compounds PM 6640 Flexible PVC, Extrusion

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

Material Notes:

Window gaskets

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fainplast-Compounds-PM-6640-Flexible-PVC-Extrusion.php

| Physical Properties | Metric | English | Comments |
|---------------------|------------------|------------------------------------|------------|
| Density | 1.31 - 1.35 g/cc | 0.0473 - 0.0488 lb/in ³ | ISO R 1183 |

| Mechanical Properties | Metric | English | Comments |
|---------------------------|----------|----------|-----------|
| Hardness, Shore A | 64 - 68 | 64 - 68 | ISO R 868 |
| Tensile Strength at Break | 12.0 MPa | 1740 psi | ISO R 527 |
| Elongation at Break | 350 % | 350 % | ISO R 527 |

| Thermal Properties | Metric | English | Comments |
|-------------------------|----------|----------|----------------------|
| Brittleness Temperature | -32.0 °C | -25.6 °F | Cold Flex; ISO 458/2 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China