## Ferro EG 0026 Glaze and Sealant Glass

Category : Ceramic , Glass , Glaze

## Material Notes:

Glass Type: Ca-B-Al-Si Typical Powder Form: MVG Typical Application: Al2O3 Ferro's electronic and specialty glass group has produced

over 3,000 formulations. Many are used as protective and insulating over glazes, binding agents and sealants for a variety of ceramic,

metal, glass parts and substrates. Information provided by Ferro Corporation

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Ferro-EG-0026-Glaze-and-Sealant-Glass.php

Physical Properties	Metric	English	Comments
Density	2.64 g/cc	0.0954 lb/in³	
Particle Size	5.0 µm	5.0 µm	50% of particles
	<= 25 µm	<= 25 µm	

Thermal Properties	Metric	English	Comments
CTE, linear	7.20 µm/m-°C	4.00 µin/in-°F	at Set Pt.
	6.30 µm/m-°C	3.50 µin/in-°F	
	@Temperature 260 °C	@Temperature 500 °F	
Softening Point	770 °C	1420 °F	
Annealing Point	665 °C	1230 °F	
Transformation Temperature	640 °C	1180 °F	

Processing Properties	Metric	English	Comments
Processing Temperature	900 °C	1650 °F	Typical Firing Temperature

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China