

Ferro EG 2410 Specialty Glass

Category: Ceramic, Glass, Glaze

Material Notes:

Glass Type: Si-MG-Al Typical Powder Form: MVG Typical Application: Sintering Aid / Glaze Ferro offers a wide range of compositions for specialty applications including sintering aids used in the glass-phase bonding of refractory ceramic oxides and glass-ceramics for substrates. Information provided by Ferro Corporation

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ferro-EG-2410-Specialty-Glass.php

Physical Properties	Metric	English	Comments
Density	2.70 g/cc	0.0975 lb/in³	
Particle Size	5.0 µm	5.0 µm	50% of particles
	<= 25 Âμm	<= 25 Âμm	

Thermal Properties	Metric	English	Comments
CTE, linear	5.00 Âμm/m-°C	2.78 Âμin/in-°F	at Set Pt.
	4.65 Âμm/m-°C	2.58 µin/in-°F	
	@Temperature 260 °C	@Temperature 500 °F	
Softening Point	>= 1000 °C	>= 1830 °F	
Transformation Temperature	620 °C	1150 °F	

Processing Properties	Metric	English	Comments
Processing Temperature	1300 °C	2370 °F	Typical Firing Temperature

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China