

Ferro EG 2705 Glaze and Sealant Glass

Category : Ceramic , Glass , Glaze

Material Notes:

Glass Type: Ca-Al-Si Typical Powder Form: MVG Typical Application: Al₂O₃ Ferro's electronic and specialty glass group has produced over 3,000 formulations. Many are used as protective and insulating over glazes, binding agents and sealants for a variety of ceramic, metal, glass parts and substrates. Information provided by Ferro Corporation

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ferro-EG-2705-Glaze-and-Sealant-Glass.php

Physical Properties	Metric	English	Comments
Density	2.81 g/cc	0.102 lb/in ³	
Particle Size	5.0 Åµm	5.0 Åµm	50% of particles
	<= 25 Åµm	<= 25 Åµm	

Thermal Properties	Metric	English	Comments
CTE, linear	7.50 Åµm/m-Å°C	4.17 Åµin/in-Å°F	at Set Pt.
	6.95 Åµm/m-Å°C	3.86 Åµin/in-Å°F	
	@Temperature 260 Å°C	@Temperature 500 Å°F	
Softening Point	925 Å°C	1700 Å°F	
Annealing Point	825 Å°C	1520 Å°F	
Transformation Temperature	800 Å°C	1470 Å°F	

Processing Properties	Metric	English	Comments
Processing Temperature	1300 Å°C	2370 Å°F	Typical Firing Temperature

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China