

Ferro EG 2770 Specialty Glass

Category: Ceramic, Glass

Material Notes:

Glass Type: Si-Al-Mg-Ca Typical Powder Form: TF Typical Application: Sintering Aid Ferro offers a wide range of compositions for specialty applications including sintering aids used in the glass-phase bonding of refractory ceramic oxides and glass-ceramics for substrates.Information provided by Ferro Corporation

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ferro-EG-2770-Specialty-Glass.php

Physical Properties	Metric	English	Comments
Density	2.60 g/cc	0.0939 lb/in³	
Particle Size	15 Âμm	15 Âμm	50% of particles
	<= 150 Âμm	<= 150 Âμm	

Thermal Properties	Metric	English	Comments
CTE, linear	4.50 Âμm/m-°C	2.50 Âμin/in-°F	at Set Pt.
	4.15 Âμm/m-°C	2.31 µin/in-°F	
	@Temperature 260 °C	@Temperature 500 °F	
Softening Point	970 °C	1780 °F	
Transformation Temperature	825 °C	1520 °F	

Processing Properties	Metric	English	Comments
Processing Temperature	>= 1000 °C	>= 1830 °F	Typical Firing Temperature

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China