

Fine Organics FINALUX GH 41 Lubricant Additive

Category : Fluid , Lubricant , Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Applications: Internal lubricant for rigid PVC injection molded fittings, calendered, blown films/sheets, PVC bottles and other Sn-mercaptide stabilized rigid PVC products. Excellent synergistic co-stabilizing properties with Sn-mercaptides. Information provided by Fine Organics

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fine-Organics-FINALUX-GH-41-Lubricant-Additive.php

Physical Properties	Metric	English	Comments
Additive Loading	1.0 - 1.5 %	1.0 - 1.5 %	R PVC

Thermal Properties	Metric	English	Comments
Melting Point	74.0 - 84.0 Â°C	165 - 183 Â°F	

Descriptive Properties	Value	Comments
Influence on Transparency	Clear	
Lubricating Effect	Internal	
Physical Form	Solid	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China