

Flint Hills AP4135-HS Polypropylene Impact Copolymer

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer , Polypropylene, Impact Modified; Molded/Extruded

Material Notes:

Features: Excellent processability, good low temperature impact strength. Applications: Injection Molding: Large, thin wall parts and house wares
Information Provided by Flint Hills Resources

Order this product through the following link:

http://www.lookpolymers.com/polymer_Flint-Hills-AP4135-HS-Polypropylene-Impact-Copolymer.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D1505
Melt Flow	35 g/10 min	35 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	96	96	ASTM D785
Tensile Strength, Yield	23.0 MPa	3340 psi	ASTM D638
Elongation at Yield	13 %	13 %	ASTM D638
Izod Impact, Notched	0.800 J/cm @Temperature 23.0 Â°C	1.50 ft-lb/in @Temperature 73.4 Â°F	ASTM D256
Gardner Impact	28.0 J @Temperature -30.0 Â°C	20.7 ft-lb @Temperature -22.0 Â°F	ASTM D5420
Tangent Modulus	1172 MPa	170000 psi	ASTM D790

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	80.0 Â°C	176 Â°F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China