

Flint Hills P6E5A-004 Impact Copolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer

Material Notes:

Impact copolymer, UL certified. Features: LTHA, controlled rheology, and extra high impact strength. Applications: Injection molding: automotive, toys, and containers. Former Huntsman polypropylene products are now produced by Flint Hills Resources.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Flint-Hills-P6E5A-004-Impact-Copolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D1505
Melt Flow	15 g/10 min	15 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	62	62	ASTM D785
Tensile Strength, Yield	19.0 MPa	2760 psi	ASTM D638
Elongation at Yield	8.0 %	8.0 %	ASTM D638
Flexural Modulus	0.670 GPa	97.2 ksi	Tangent; ASTM D790
Gardner Impact	>= 36.0 J @Temperature -30.0 Â°C	>= 26.6 ft-lb @Temperature -22.0 Â°F	ASTM D3029

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	67.0 Â°C	153 Â°F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China