

## Formosa Plastics Formolene® 1102KR Cast Film Polypropylene

Category: Polymer, Film, Thermoplastic, Polypropylene (PP), Polypropylene, Film Grade

## **Material Notes:**

HomopolymerApplications: Cast film applications such as slit tape fabric stock and cordage. Formolene 1102KR is a highly isotactic polypropylene homopolymer designed primarily for cast film applications such as slit tape fabric stock and cordage. It contains a unique combination of stabilizers which give it low water carry over as well as excellent melt stability. Meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact. Specimens were injection molded according to the conditions specified in ASTM D4101. Information provided by Formosa Plastics Corporation, USA.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Formosa-Plastics-Formolene-1102KR-Cast-Film-Polypropylene.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in³	ASTM D1505
Melt Flow	4.0 g/10 min	4.0 g/10 min	I <sub>2</sub> ; ASTM D1238
	@Temperature 230 °C	@Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	105	105	ASTM D785
Tensile Strength, Yield	34.5 MPa	5000 psi	2" (50mm) per min.; ASTM D638
Elongation at Yield	9.0 %	9.0 %	2" (50mm) per min.; ASTM D638
Flexural Modulus	1.38 GPa	200 ksi	1.3mm per min, 1% secant; ASTM D790
Izod Impact, Notched	0.427 J/cm	0.800 ft-lb/in	ASTM D256

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China