

## Garlock 2103 C.I. SBR/NBR Sheet Rubber, Polyester Insert

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Styrene Butadiene Rubber

### Material Notes:

Garlock cloth-inserted materials are designed to add stability where mechanical fastening is necessary, and to reduce gasket creep where heavy flange loading is required. Style #2103 C.I. is a smooth-finish SBR/NBR sheet constructed with polyester fabric. Designed to reduce creep in flanges. Information provided by Garlock Rubber Technologies

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Garlock-2103-CI-SBRNBR-Sheet-Rubber-Polyester-Insert.php](http://www.lookpolymers.com/polymer_Garlock-2103-CI-SBRNBR-Sheet-Rubber-Polyester-Insert.php)

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70 - 80	70 - 80	
Tensile Strength	>= 6.89 MPa	>= 1000 psi	
	8.96 MPa	1300 psi	Typical
Elongation at Break	>= 200 %	>= 200 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	82.2 Â°C	180 Â°F	
Minimum Service Temperature, Air	-28.9 Â°C	-20.0 Â°F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China