

Garlock 244 Neoprene Rubber - Commercial Grade

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Styrene Butadiene Rubber

Material Notes:

Soft blend of neoprene, nitrile and SBR rubbers for use as bumpers, pads, and in sealing and general gasket applications. It is not recommended in applications where high oil resistance is required. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-244-Neoprene-Rubber-Commercial-Grade.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	35 - 45	35 - 45	
Tensile Strength	>= 5.52 MPa	>= 800 psi	
	6.21 MPa	900 psi	Typical
Elongation at Break	>= 350 %	>= 350 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	87.8 Â°C @Pressure <= 1.03 MPa	190 Â°F @Pressure <= 150 psi	
Minimum Service Temperature, Air	-28.9 Â°C @Pressure <= 1.03 MPa	-20.0 Â°F @Pressure <= 150 psi	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China