

Garlock 2564 C.I. NBR/CR/SBR Sheet Rubber, Polyester Insert

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE) , Styrene Butadiene Rubber

Material Notes:

Garlock cloth-inserted materials are designed to add stability where mechanical fastening is necessary, and to reduce gasket creep where heavy flange loading is required. Style #2264 is a smooth finish NBR/CR/SBR sheet, constructed with polyester. For moderate oil resistant applications. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-2564-CI-NBRCRSBR-Sheet-Rubber-Polyester-Insert.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	55 - 65	55 - 65	
Tensile Strength	>= 6.89 MPa	>= 1000 psi	
	8.27 MPa	1200 psi	Typical
Elongation at Break	>= 300 %	>= 300 %	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 Â°C	250 Â°F	
Minimum Service Temperature, Air	-28.9 Â°C	-20.0 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China