

Garlock GYLON[®] 3503 PTFE Gasketing, Barium Sulfate Filler, Oxygen Service

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

Material Notes:

PTFE with barium sulfate filler - Oxygen service. Improved sealing performance over conventional PTFE. Unique manufacturing process minimizes cold flow problems typical of skived and expanded PTFE sheets. Excellent bolt torque retention. Withstands a wide range of chemicals for extended service life. Media: Strong caustics, Moderate acids, Chlorine, Gases, Water, Steam, Hydrocarbons, Cryogenics and aluminum fluoride. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-GYLON-3503-PTFE-Gasketing-Barium-Sulfate-Filler-Oxygen-Service.php

Physical Properties	Metric	English	Comments
Permeability	0.015	0.015	Gas Permeability, cc/min; DIN 3535 Part 4

Mechanical Properties	Metric	English	Comments
Tensile Strength	13.8 MPa	2000 psi	across grain; ASTM F152

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 Â°C @Pressure 8.27 MPa	500 Â°F @Pressure 1200 psi	Continuous
Minimum Service Temperature, Air	-268 Â°C	-450 Â°F	

Descriptive Properties	Value	Comments
Color	Off-White	
Compressibility, %	4-10	ASTM F36
Creep Relaxation, %	11	ASTM F38
Sealability ASTM F37B, ml/hr	0.04	ASTM Fuel A

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China