

Garlock GYLON® 3535 PTFE Joint Sealant

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE

Material Notes:

Pure PTFE is chemically inert, withstands a wide range of chemicals
Conforms to FDA regulations
Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-GYLON-3535-PTFE-Joint-Sealant.php

Physical Properties	Metric	English	Comments
Permeability	0.050	0.050	Gas Permeability, cc/min; DIN 3535 Part 4

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 Â°C @Pressure 5.52 MPa	500 Â°F @Pressure 800 psi	
Minimum Service Temperature, Air	-268 Â°C	-450 Â°F	

Compliance Properties	Metric	English	Comments
FDA	Yes	Yes	

Descriptive Properties	Value	Comments
Sealability ASTM F37B, ml/hr	0.1	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China